Hygro-thermometer

USA & Taiwan Patent Pending

NEW

8760

USA & Taiwan Patent Pending

NEW

87601

Wet Bulb Hygrometer w/Memory 8760/87601

- ⚠ Modern look smartest digital wet bulb hygrometer
- ⚠ Easy-to-read big LCD display
- ⚠ No chart reference is needed
- ⚠ Designed with two thermistor type sensors to get accurate and quick temperature & humidity reading
- ⚠ Built-in fan to speed up the response time to 2 mins
- ⚠ 100 points auto logging memories for 8760
- ⚠ 16000 points auto logging memories for 87601
- ⚠ Auto logging sampling rate selectable
- ⚠ Temp. and humidity high/low alarm setting are available
- ⚠ Dual color LED indicator for logging and alarm
- ⚠ Maximum / minimum functions are available
- ⚠ Temperature unit °C/°F selectable
- ⚠ Self-calibration is not necessary
- ⚠ Battery low indicator
- ⚠ 16000 points memory could be download to PC for analysis
- ⚠ Powered by 4pcs AAA batteries or 5V adaptor

application:

-excellent for green house & any high humidity environment!
-excellent for harsh & dusty environment!
-excellent for educational purpose!
-condensation caused by water/ pesticide/fertilizer
* spray has limited effect on humidity reading!*
-dust scrap has limited effect on humidity reading!

High RH% Green House

Optional

USB CABLE & SOFTWARE
P/N: VZUSBNLD (for 87601)

Model	8760	87601
Temp. range	5~50°C	
Temp. resolution	0.1°C/°F	
Temp. accuracy	+/-0.6°C	
Humidity. range	0%RH~100%RH	
Humidity resolution	0.1%RH	
Humidity accuracy	+/-3%(10~100%RH@25°C), the rest is +/-5%	
Response time	120 seconds typical	
LCD size (mm)	25(H)x40(W)	
Memory	100 points	16000 points
Operation temp.	5~50°C	
Operation RH%	Humidity < 100%	
Storage temp.	0~50°C	
Storage RH%	Humidity < 80%	
Water Tank Refill Time	Every two weeks	
Dimension(mm)	48.4x178.5x24.7(H)	
Weight	~250g	
Battery	AAA x 4pcs or 5V adaptor	
Standard Package	Meter/Water tank/ Battery/Manual/Paper box /Cotton thread	
Optional Package	5V universal adaptor software cable & CD (87601 only)	

2014.08 V4