

4ch Thermo-Datalogger

NEW

Japan & Taiwan Patented



88598

4 channel K thermometer SD logger 88598

- ▲ Super big LCD portable / wallmount SD card logger measures temperature via k type thermocouple
- ▲ 4 channel k type thermocouple to use at once
- ▲ Unlimited manual memories in SD card
- ▲ Unlimited autologging memories in SD card
- ▲ Hold function freezes current readings
- ▲ Checking max / min value from power on
- ▲ Beeper and LED alarm are both available
- ▲ One button press to display T1-T2
- ▲ Display temperature change from baseline
- ▲ Programmable temperature High/Low alarm limit
- ▲ Temperature offset function for adjustment purpose
- ▲ Over-range indication with error messages
- ▲ Blue backlight function works in dark area
- ▲ 12hour/24hour time format selectable
- ▲ Real time display (year-mon-date, hour-min)
- ▲ 20mins auto power off to save power
- ▲ Temperature units (C/F) selection
- ▲ Powered by 4pcs AA batteries or 9V adaptor
- ▲ Low battery indicator


Wallmount with big display!!

No bothering computer setting!!

Auto log anytime anywhere!!

Leave your PC at home !!

Optional



K BEAD TYPE THERMOCOUPLE

P/N:VE60A000

TEMP. RANGE:-50~200°C

OTHER CUSTOM MADE PROBE

: IMMERSION,PENETRATE,

SURFACE.....ETC ARE AVAILABLE

UPON REQUEST

9V UNIVERSAL ADAPTOR

P/N:VB1099EX

Model	88598
K temp. range	-200~1370°C , -328~2498°F
K temp. resolution	0.1°C , 0.1°F
K temp. accuracy (under 18~28°C ambient temp.)	±(0.3% rdg +1°C)
Sampling rate	Programmable from 1 second up
LCD size (mm, HxW)	47x104
Operating temp.	0~50°C
Operating RH%	Humidity < 80%
Storage temp.	-20~50°C
Storage RH%	Humidity < 90%
Dimension(mm,LxWxT)	152x100x39
Weight	~300g
Battery	4pcs AA alkaline batteries or 9V adaptor
Standard Package	Meter, 2pcs bead type K thermocouple, battery, manual. SD card, plain box
Optional Accessory	K type thermocouple (custom made thermocouple is available upon request)