





Digital Hand-held "Pocket" Salinity Refractometer



Features

. () .

2005

- * Calibration with water only
- * Measurement in 3 seconds
- * Extremely water resistant (IP65)
- * Light & Compact, 100g
- * Ergonomically designed for easy, one-handed operation
- * Convenient storage case
- * Automatic Temperature Compensation (ATC)
- * Designed with a strap holder option



Measurement Range	Salinity 0 to 100‰
Resolution	Salinity 1‰
Measurement Accuracy	Salinity ±2‰
Measurement Temperature	10.0 to 40.0°C (ATC)
Sample Volume	0.3ml or more
Measurement Time	3 seconds
Power Supply	AAA alkaline battery × 2
Battery Life	Approx. 11,000 measurements
	(Using a new alkaline battery)
International Protection Class	IP65 Water Resistant
Dimensions and Weight	55 (W)×31(D)×109(H)mm, 100g (Main unit only)

HACCPGMPGLP

0.3°C

ZERO

PAL-06S

SALINITY

STAR

ckoł

All ATAGO refractometers are designed and manufactured in Japan.

ATAGO CO., LTD.

Headquarters: The Front Tower Shiba Koen, 23rd Floor 2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan TEL : 81-3-3431-1943 FAX : 81-3-3431-1945 overseas@atago.net http://www.atago.net/

CATAGO U.S.A., Inc. TEL : 1-425-637-2107 customerservice@atago-usa.com

TEL: 91-22-2833-8038 / 8076 customerservice@atago-india.com

CATAGO (THAILAND) Co., Ltd. TEL : 662-982-8718-9 customerservice@atago-thailand.com

CATAGO BRASIL Ltda. TEL : 55 16 3916-6000 customerservice@atago-brasil.com

 ATAGO ITALIA s.r.I. TEL: 39 2 36557267 customerservice@atago-italia.com
ATAGO CHINA Guangzhou Co, Ltd. TEL: 86 20-38106065 info@atago-china.com



* Specifications and appearance are subject to change without notice.



ATAGO products comply with HACCP, GMP, and GLP system standards.

Actual

size