

CENTER 322 Datalogger Sound Level Meter



If one needs long time on site sound monitoring, CENTER 322 will be the choice. With its built-in 32000 records deep memory, it can gather all the data you need just by this tester and a tripod. After the data is collected, the user can download the data to the computer at his convenient place.

FEATURES:

- RS-232 Interface
- 32,000 Records Datalogger
- Bargraph Indication
- MAX/MIN Function
- Auto Ranging (30 ~ 130dB)
- Resolution 0.1dB
- Clock Display
- Level Range Display



SPECIFICATIONS

Level Range	Lo=30 ~ 80dB ; Med=50 ~ 100dB ; Hi=80 ~ 130dB
Accuracy	±1.5dB (ref 94dB@1KHz)
Frequency Weighting	A / C
Time Weighting	Fast, Slow
Dynamic Range	50dB
Frequency Range	31.5Hz to 8KHz
Microphone	Electret condenser microphone
Auxiliary Outputs	AC/DC Output
Battery	9V battery
Dimensions	275x64x30 mm
Weight	Approx.280g

STANDARD ACCESSORIES

Battery, Operation Manual, Carrying Case, Calibration Screwdriver, Windscreen, 3.5 ϕ plug, Software, RS-232 cable.


CENTER 325 Compact Size Sound Level Meter



CENTER 325 is our entry level sound level meter. We have tried to keep as much feature as possible and on the same time reduce the system complexity as much as possible. 325 is the result.

FEATURES:

- Mini Size
- Low Cost High Performance
- MAX/MIN Function
- Resolution 0.1dB
- Level Range Display
- IEC 651 TYPE II



SPECIFICATIONS

Level Range	Lo=32 ~ 80dB ; Med=50 ~ 100dB ; Hi=80 ~ 130dB
Accuracy	±1.5dB (ref 94dB@1KHz)
Frequency Weighting	A / C
Time Weighting	Fast, Slow
Dynamic Range	50dB
Frequency Range	31.5Hz to 8KHz
Microphone	Electret condenser microphone
Auxiliary Outputs	AC signal output
Battery	9V battery
Dimensions	232x54x34 mm
Weight	Approx.200g

STANDARD ACCESSORIES

Battery, Operation Manual, Calibration Screwdriver, Windscreen.