

SOUND LEVEL METER

CENTER®

CENTER 328 Sound Level Meter



CE

FEATURES:

- Mini Size
- Easy to use
- Low Cost High Performance
- MAX Function
- Autoranging
- Maximum Recording
- 4-digit LCD With a Resolution of 0.1 dB
- Internal Calibrator (94dB@1 kHz)



SPECIFICATIONS

Measure Range	32 ~ 130dB
Accuracy	± 1.4dB (ref 94dB@1kHz)
Frequency Weighting	A
Time Weighting	FAST
Frequency Range	31.5Hz to 8KHz
Microphone	1/2 Electret condenser microphone
Battery	1.5Vsize AAA battery x 2
Dimensions	206 x 42 x 25 mm
Weight	Approx. 100g

STANDARD ACCESSORIES

Battery, Operation Manual, Calibration Screwdriver, Windscreen.

CENTER 326 Sound Level Calibrator



CE

FEATURES:

- 94dB and 114dB Sound Calibrator at 1kHz
- Accurate and Simple to Use
- Fits 1 inch and 1/2 inch Microphones
- IEC 60942(2003) Class 2,ANSI 1.40-1984



SPECIFICATIONS

Output Sound Pressure Levels	114dB and 94dB re 20uPa under reference Conditions
Output Frequency	1000Hz ± 2%
Total Harmonic Distortion	< 3%
Reference Condition	Temperature 23°C(73°F) Static press 103hpa Relative humidity 50%
Accuracy of sound pressure level	Under stated reference environment conditions ± 0.5dB
Battery test	Operate: Green LED indicator Low battery: Red LED indicator
Battery	9V battery
Dimensions	113x63x44 mm
Weight	Approx. 170g

STANDARD ACCESSORIES

Battery, Operation Manual, Carrying Case, 1/2 inch Microphone adapter.