



Function	Range	Accuracy	Note
Embedded Sensor	-10°C~60°C (14°F~140°F)	±0.8°C (±1.5°F)	—
Relative Humidity	20%~80%R.H.	±3%R.H.	at 30°C
	<20%, >80%R.H.	±5%R.H.	

Environment Condition Icon Indication			
R.H.at	<45% R.H.	45%~65% R.H.	>65% R.H.
Icon	☹️	😊	☹️
Condition	Dry	Comfortable	Wet

Features

- Big LCD Display for Easy Reading
- Wall Mount or Stand up with Brace
- Recording Max/Min Value of Temperature and Humidity
- Sampling rate (Temp/Humidity): 10 seconds or 1 minute (setting at manufactory)
- Celsius and Fahrenheit for Option
- Clock with 12 Hours & 24 Hours for Option
- Alarm Clock Set
- Low Battery Indication
- Environment Condition Icon Indication (Dry / Comfortable / Wet)
- 100 Sets (0~99) An-Hour Interval Memory of Temperature/Humidity/Condition
- Recall Memory Data

Specifications

- Temperature Range (embedded sensor): -10°C~60°C (14°F~140°F)
- Humidity Range: 0%~100%R.H.
- Operation Conditions: -10°C~60°C (14°F~140°F), <95% R.H. (no condensation)
- Storage Conditions: -15°C~65°C(5°F~149°F), <70% R.H. (no condensation)

Dimension / Weight

- Dimension: 120 (L) x 100 (W) x 26 (H)mm
- Weight: approx. 150g (excluding batteries)

Accessories

- 1.5V AAA batteryx2
- User Manualx1

