

Product data sheet

## Dino-Lite AM4113T

For the serious precision applications the Dino-Lite Pro AM4113T has a high resolution of 1,3 megapixel and an adjustable magnification of appr. 10 to 70 times as well as 200x. This model also provides the possibility to calibrate the microscope for measurements. Most used model in the industrial field.



<b>Model</b>	AM4113T
<b>Resolution</b>	1,3 megapixel (1280x1024 pixels)
<b>Magnification</b>	10x~70x, 200x
<b>Interface</b>	USB 2.0, High speed USB transmission
<b>Nr. of LED's</b>	8
<b>LED on/off switchable</b>	√
<b>LED color</b>	White
<b>Housing</b>	Composite
<b>Microtouch</b>	√
<b>Magnification lock</b>	√
<b>Output</b>	Picture, video and time-lapsed video
<b>Video Frame Rate</b>	up to 30 frames-per-second, 15fps at 1.3M
<b>Measurement</b>	√ (line, radius, circle, 3-point circle, etc.)
<b>Calibration</b>	√
<b>Filter/Diffuser</b>	-
<b>Compatibility</b>	Windows XP, Vista, 7, 8 and recent MAC OS
<b>Software (Included)</b>	Windows: DinoCapture, Mac: DinoXcope