

STANDARD LINE 4 BUTTONS

STANDARD HANDLE TYPE

FIXED HEAD



MODEL NO.	DE2-030 WE2-030		DE3-135 WE3-135		DE4-135 WE4-135		DE4-200 WE4-200		DE4-340 WE4-340		DE6-500 WE6-500 IE6-500	DE6-850 WE6-850 IE6-850	IE8-1200	IE8-1500	IE8-2000	
	AN	BN	AN	BN	AN	BN	AN	BN	AN	BN	BN	BN	BN	BN	BN	
ACCURACY	CW:±1% CCW:±2%	CW:±2% CCW:±3%	CW:±1% CCW:±2%	CW:±2% CCW:±3%	CW:±1% CCW:±2%	CW:±2% CCW:±3%	CW:±1% CCW:±2%	CW:±2% CCW:±3%	CW:±1% CCW:±2%	CW:±2% CCW:±3%	CW:±2.5% CCW:±3.5%	CW:±2.5% CCW:±3.5%	CW:±2.5% CCW:±3.5%	CW:±2.5% CCW:±3.5%	CW:±2.5% CCW:±3.5%	
SQUARE DRIVE (INCHES)	1/4		3/8		1/2		1/2		1/2		3/4		3/4		1	
TORQUE MEASURING RANGE	1.5~30 N-m 1.11~22.12 ft-lb 13.3~265.5 in-lb 15.3~306.1 kg-cm		6.8~135 N-m 5~99.5 ft-lb 60~1195 in-lb 69~1378 kg-cm		6.8~135 N-m 5~99.5 ft-lb 60~1195 in-lb 69~1378 kg-cm		10~200 N-m 7.4~147.5 ft-lb 88~1770 in-lb 102~2041 kg-cm		17~340 N-m 12.5~250.7 ft-lb 150~3009 in-lb 173~3469 kg-cm		25~500 N-m 18.4~368.7 ft-lb 221~4424 in-lb 255~5102 kg-cm	42.5~850 N-m 31.3~626.8 ft-lb 376~7521 in-lb 434~8674 kg-cm	60~1200 N-m 44~885 ft-lb	75~1500 N-m 55~1106 ft-lb	100~2000 N-m 74~1476 ft-lb	
RESOLUTION	0.01 N-m / 0.01 ft-lb 0.1 in-lb / 0.1kg-cm								0.1 N-m / 0.1 ft-lb 1 in-lb / 1kg-cm				1 N-m / 1 ft-lb			
COMMUNICATION	No															
UNIT SELECTION	N-m, in-lb, ft-lb, kg-cm											N-m, ft-lb				
OPERATION MODE	Peak hold / Track															
GEAR TEETH	36										48					
LENGTH (MM)	390		415		415		530		650		950	1220	1800	1800	1800	
WEIGHT (KG)	0.79		0.97		0.99		1.43		1.60		2.95	4.26	9	9	9	
BATTERY	AA x 2															

* Torque Accuracy: [A] ±1% (CW); [B] ±2%(CW) or ±2.5%(CW)

* Memory: [N] no memory, no communication

* Accuracy is guaranteed from 20% to 100% full Scale.