

**No. 6400-00 HANDY TYPE DIGITAL PH METER MODEL SK-620PH**

**SPECIFICATIONS**

Measuring range: pH: 0.00 to 14.00pH  
 Temp.: 0.0 to 50.0°C  
 Accuracy: pH: ±(0.3+1 digit)pH at 0 to 2pH  
 ±(0.1+1 digit)pH at 2 to 12pH  
 ±(0.4+1 digit)pH at 12 to 14pH  
 Temp.: ±0.5°C at 20 to 30°C, ±0.7°C at other  
 Resolution: 0.01pH / 0.1°C  
 Elements: pH: Glass electrode  
 Temp.: Thermistor  
 Power requirements: 9 VDC (6F22 (006P) x 1 pc.) or AC adapter (optional)  
 Materials: Case: ABS resin Probe: Glass  
 Dimensions: 72(W) x 182(H) x 31.5(D) mm  
 Weight: about 220 g (including battery)  
 Standard accessories: PHP-31 probe, bottle for glass electrode, vinyl cover, carrying case,  
 6F22 (006P) battery x 1, standard liquid set (Phthalate solution,  
 Neutral phosphate solution, Carbonate solution)



**No. 6410-00 PEN TYPE DIGITAL PH METER MODEL SK-610PHII**

**SPECIFICATIONS**

Measuring range: pH: 2.0 to 12.0pH  
 Temp.: 0.0 to 50.0°C  
 Accuracy: pH: ±2pH  
 Temp.: ±0.6°C at 20 to 30°C, ±0.8°C at other  
 Resolution: 0.01pH / 0.1°C  
 Elements: pH: Glass electrode  
 Temp.: Thermistor  
 Power requirements: 6VDC (3V Lithium button battery CR2032 x 2)  
 Materials: Case: ABS resin Probe: Glass  
 Dimensions: 37(W) x 150(H) x 42(D) mm  
 Weight: about 77 g (including batteries)  
 Standard accessories: Vinyl pouch, Lithium button battery x 2



**POCKET TYPE DIGITAL PH METERS**

- No. 6416-00 MODEL SK-630PH**
- No. 6418-00 MODEL SK-631PH**
- No. 6420-00 MODEL SK-632PH**

**FEATURES**

- Calibration function
- HOLD function
- Auto power-off function
- Auto temperature compensation (ATC)  
 (Not applicable for model SK-630PH)



SK-630PH



SK-631PH



SK-632PH

**SPECIFICATIONS**

Model		SK-630PH	SK-631PH	SK-632PH
Measuring range	pH	2.0 to 12.0pH	2.0 to 12.0pH	2.00 to 12.00pH
	Temp.	–	0.0 to 50.0°C	0.0 to 50.0°C
Accuracy	pH	±0.6pH	±0.5pH	±0.4pH
	Temp.	–	±1.0°C	±0.5°C
Resolution	pH	0.1pH	0.1pH	0.01pH
	Temp.	–	0.5°C	0.1°C
Elements	pH	Glass electrode		
	Temp.	–	Thermistor	
Measuring ambient		0 to 50°C		
Power requirement		6VDC (Button battery LR44 1.5VDC x 4)		
Battery life		about 20 hours in continuous use		
Materials		Case: ABS resin Sensor: Glass		
Dimensions		36 (W) x 150 (H) x 25 (D) mm		
Weight		approx. 65 g (including batteries)		
Standard accessories		Button battery LR44 (GPS76E) x 4		

