

**No. 2150-B BIMETAL THERMOMETER FOR ASPHALT****SPECIFICATIONS**

Case diameter:	Ø80 mm
Dial diameter:	Ø75 mm (Black scale plate is provided)
Case material:	SPCC Nickel plating
Cover material:	SUS304
Window material:	Glass
Stem dimensions:	Ø8 x 200 mm, pointed end
Stem material:	SUS304
	No. 2150-10 Black scale plate
	No. 2150-20 White scale plate
Temp. range:	0 to 200°C (5/1)

**No. 2250-10 BIMETAL THERMOMETER FOR ASPHALT (LARGE TYPE II)****SPECIFICATIONS**

Case diameter:	Ø175 mm
Dial diameter:	Ø150 mm
Case & cover material:	Polyamide resin
Window material:	Glass
Stem dimensions:	Ø8 x 200 mm, pointed end
Stem material:	SUS304
Temp. range:	0 to 200°C (2/1)

**No. 2180-B BIMETAL THERMOMETERS FOR GRAIN****SPECIFICATIONS**

Case diameter:	Ø80 mm
Dial diameter:	Ø75 mm
Case material:	SPCC Nickel plating
Cover material:	Aluminum
Window material:	Glass
Stem dimensions:	No. 2180-00 Ø8 x 250 mm
	No. 2185-00 Ø8 x 500 mm
Stem material:	SUS304
Temp. range:	-10 to 50°C (1/1)

**No. 2340-B BIMETAL THERMOMETERS FOR SURFACE TEMPERATURE WITH MAGNET****SPECIFICATIONS**

Case diameter:	Ø64 mm x 16 mm (t)
Dial diameter:	Ø60 mm
Case material:	Bs chrome plating
Cover material:	SUS304
Window material:	Glass
Bulb dimensions:	Ø25 x 7 mm (t)
Temp. range:	No. 2340-20 0 to 200°C (2/1)
	No. 2340-40 0 to 400°C (5/1)

**No. 2060-B POCKET BIMETAL THERMOMETERS****SPECIFICATIONS**

Case diameter:	Ø26 mm
Dial diameter:	Ø24 mm
Case & cover material:	SUS304
Window material:	Glass
Stem dimensions:	Ø4 x 130 mm, pointed end
Stem material:	SUS304
Sheath material:	Polyvinyl chloride
Accessories:	Plastic window cover
Temp. range:	No. 2060-45 -40 to 50°C (1/1)
	No. 2060-11 -10 to 110°C (1/1)
	No. 2060-20 0 to 200°C (5/1)