

SIGMA II THERMOGRAPH

CE

SPECIFICATIONS

Cat. No.:	No. 7230-00
Model:	NSII-TQ
Measuring range:	-15 to 40°C (option: -10 to 50°C)
Clock:	Quartz type 1 day, 7 day and 32 day by change-over switch
	Battery: "C" size battery x 2 Battery life: 1 year for continuous use
Sensor:	Aged bimetallic strip
Accuracy:	±1°C (10 to 30°C) ±2°C (other range)
Chart graduation:	1°C
Recording pen:	Cartridge pen (violet)
Dimensions:	336 (W) x 148 (D) x 295 (H) mm
Weight:	Approx. 2.9 kg
Accessories:	7 day chart for 1 year use (55 sheets/pad) "C" size battery x 2

SIGMA II HYGROGRAPH

CE

SPECIFICATIONS

Cat. No.:	No. 7234-00
Model:	NSII-HQ
Measuring range:	0 to 100% for relative humidity
Clock:	Quartz type 1 day, 7 day and 32 day by change-over switch
	Battery: "C" size battery x 2 Battery life: 1 year for continuous use
Sensor:	Human hair bundle
Accuracy:	±3% RH (20 to 95%RH at 15 to 25°C) ±5% RH (other range)
Chart graduation:	1% RH
Recording pen:	Cartridge pen (violet)
Dimensions:	336 (W) x 148 (D) x 295 (H) mm
Weight:	Approx. 2.9 kg
Accessories:	7 day chart for 1 year use (55 sheets/pad) "C" size battery x 2

SIGMA II BAROGRAPH

CE

SPECIFICATIONS

Cat. No.:	No. 7237-00
Model:	NSII-BQ
Measuring range:	940 to 1045 hPa
Clock:	Quartz type 1 day, 7 day and 32 day by change-over switch
	Battery: "C" size battery x 2 Battery life: 1 year for continuous use
Sensor:	Bellows
Temperature compensation:	Bimetal
Accuracy:	±1 hPa (950 to 1040 hPa) ±2 hPa (other range)
Chart graduation:	1 hPa
Recording pen:	Cartridge pen (violet)
Dimensions:	336 (W) x 148 (D) x 295 (H) mm
Weight:	Approx. 3.1kg (Quartz type)
Accessories:	7 day chart for 1 year use (55 sheets/pad) "C" size battery x 2

* Spring-wound type is available for ordering.