

**SK-250WP II SERIES WATERPROOF DIGITAL THERMOMETERS**

No. 8062-00 MODEL SK-250WP II-N FOR GENERAL PURPOSE

No. 8064-00 MODEL SK-250WP II-T WITH TIMER FUNCTION

No. 8066-00 MODEL SK-250WP II-R WITH MEMORY FUNCTION

No. 8068-00 MODEL SK-250WP II-K FOR SIMPLE OPERATION

**MUTUAL FEATURES**

- Main units are waterproof construction conforming to **IP X6** rated — protected against strong jets of water.  
— limited ingress permitted. They will not be affected in function at the touch of wet hands or with splash water.
- Measured value can be held. (HOLD function)
- Power automatically turn off after 60 minutes. (AUTO POWER-OFF function)

**MUTUAL SPECIFICATIONS (MAIN UNITS)**

Cat. No.	8068-00	8062-00	8064-00	8066-00
Model	SK-250WP II-K	SK-250WP II-N	SK-250WP II-T	SK-250WP II-R
Measuring range	-40 to 250°C (depends on the probe connected: SWP II series)			
Resolution	0.1°C at -9.9 to 199.9°C    1°C at other range			
Accuracy (body)	±(0.1+1 digit)°C at -9.9 to 199.9°C ±(1+1 digit)°C at other than above			
Waterproof property	Conforming to JIS C 0920 IPX6			
Operating ambient	0 to 50°C			
Sampling time	Approx. 1 sec.			
Functions	Data Hold, Auto power-off, Low battery mark			
	Min/Max memory data			
	Clock display (24h)			
	Timer function (buzzer sounds)			
	Alarm Upper/Lower limits (buzzer)			
	Data memory (100)			
Power requirement	3VDC (AAA size battery x 2)			
Battery life	Approx. 1000 hours continuous with alkaline batteries (350 hours under use of buzzer)			
Material	ABS resin			
Dimensions	71(W)×170(H)×36(D)mm			
Weight	Approx. 145g			
Accessories	SWP II-01M probe w/test result, hand strap, vinyl cover, "AAA" size alkaline battery x 2			