



UV RADIOMETER

UVR-300



High sensitivity, Wide range, User-friendly, High performance digital UV Meter.

The UVR-300 is a handy-type UV radiometer with excellent efficiency and expansive ability.

Three different types of high-sensitivity detectors, each for differing wavelength ranges, are available to deal with specific usages.

Measuring bactericidal lamps, measurement of quantity of light of photochemical reaction, measurement of quantity of light of photoresist, and testing solarization are just a few areas where the UVR-300 stands out.



Features

Extra digit for detecting sensitivity

0.1 - 280,000 $\mu\text{W}/\text{cm}^2$

Measurement mode are selectable by Keyboard

- Correction factor (C.C.F. mode)
Input correction factor for irradiance of various ultraviolet lamps.
- Measurement of integral irradiance (mJ/cm^2 mode)
Irradiation amount of ultraviolet light can be easily measured with the integration function. Maximum integral irradiance is 1,000,000,000 mJ/cm^2 , and maximum integration time is 999,900 seconds (approx. 280 hrs.).
- Deviation measurement (Δ mode)
percentage measurement (% mode)
The amount of deviation of the ultraviolet ray irradiation surface as compared to the reference value can be calculated.



USB interface

Measured data can be retrieved from UVR-300 via USB.

Pin No.	Signal	Baud rate	38400
1	VBUS	Data length	7
2	D-	Parity	ODD
3	D+	Spread bit	1
4	GND		
5	GND		

*USB cable is not included in UVR-300 standard package.
*Mini USB series B connect mail (5pin)



Examples of use

Photochemical reaction

- Photoresist for manufacturing semiconductors
- Photosensitive materials for printing or plate making
- Photo color fading
- Evaluation of solar battery properties
- Testing for deterioration of products

Photoelectric reaction

- Exposure for electrophotography
- Printing for electrophotography

Biological reaction

- Erythema, pigmentation
- Treatment of facula, diagnosis of photo-hypersensitivity
- Aid and control in raising livestock or fish
- Suppressing turion in plants
- Photosynthesis

Measurement and analysis of germicidal effects in food processing

* Also can be used for other adjustment, inspection, research, development

Examples of light sources

- Fluorescent sun-lamp
- High-pressure mercury-vapor lamp
- Photo-polymerization
- Super-high-pressure mercury-vapor lamp
- Black light (UD-360)
- Photocopying lamp
- Xenon lamp
- Bactericidal lamp (UD-250)
- Fluorescent lamp, etc.

Good to Know

Basic relations

$$\begin{aligned} \text{Joule } [J] &= \text{Watt } [W] \times \text{Second } [s] \\ \text{Joule } [J] &= 10^7 [\text{erg}] \\ [\text{cm}^2] &= 10^{-4} [\text{m}^2] \\ \text{Hour } [h] &= 3600 [s] \end{aligned}$$

Converting units

$$\begin{aligned} 1 \text{ mW}/\text{cm}^2 &= \frac{10^{-3} W}{10^{-4} \text{m}^2} = 10 W/\text{cm}^2 \\ 1 \text{ mW} \cdot \text{h}/\text{cm}^2 &= \frac{10^{-3} W \cdot 3,600 s}{10^{-4} \text{m}^2} = 36,000 J/\text{m}^2 \\ 1 \text{ mJ}/\text{cm}^2 &= \frac{10^{-3} \mu W \cdot 1 s}{1 \text{cm}^2} = 1,000 \mu W \cdot s/\text{cm}^2 \end{aligned}$$

Standard Package

- UVR-300 (main body)..... 1 pcs
- Cap..... 1 pcs
- Leather case..... 1 pcs
- CD-ROM (USB Driver / instruction manual)..... 1 pcs
- Analog output plug..... 1 pcs
- AA battery..... 2 pcs

Detectors


3 Types of Detectors

UD-250 (220 - 300nm)

UD-360 (310 - 400nm)


UD-400 (360 - 490nm)

Three type of detectors are interchangeable and Main unit of UVR-300 is shared by three detectors.




Spectral Characteristic


Spectral sensitivity characteristics



Angular incident light characteristics




Spectral distribution of calibration light sources



* If you measure light sources having spectral properties differing to the calibration light source using an ultraviolet radiometer, the values will be relative values, not absolute. Examples of relative value measurement include: deterioration management of UV lamps, measurement of UV lamp flux distribution, measurement of illuminance irregularities of UV irradiation devices, etc.

System / Dimensions



Specifications

Display range	0.1 – 280,000μW/cm²		
	Auto/manual 4-step range		
Display	4-digit LCD Read		
Linearity	± 5% of rdg. : ± 1 digit (Auto range)		
Measurement wavelength range	UD-250 220 – 300 nm		
	UD-360 310 – 400 nm		
	UD-400 360 – 490 nm		
Angle incident light characteristics		UD-250	UD-360 / 400
	30°	±3%	±3%
	60°	±15%	±10%
Temperature Characteristics	Within ±3% (-10 to 4°C : against 23°C)		
Humidity characteristics	Within ±3%		
Analog signal output	0 to 3Vmax, 1mV / 1digit		
Interface	USB (Virtual COM port)		
Power supply	AA battery x 2		
Operating conditions	Temperature : -10 to +40°C		
	Humidity : 85% R.H. or less (no condensation)		
Dimensions	Approx. 195 mm x 70 mm x 33 mm (including detector)		
Weight	About 260 g (including detector and batteries)		
Detection element	Silicon photodiode		
Calibration light source	UD-250 GL-15		
	UD-360 FL20S·BLB		
	UD-400 Standard light source A		

Detector unit types such as UD-250, UD-360, UD-400 are available according to measurable wavelengths range, but the display unit can be used with any of them.

○Meaning of "of rdg." and "digit"

"of rdg" is for reading values. For example, " $\pm 5\%$ of rdg" means $\pm 5\%$ of reading values.

± 1 digit means reading values. "digit" means 1 count in digital and indicates that there may be error of one count in the last significant digit of the digital display.

Options

AC adapter ZV-42


AC adapter is used in long time continuous measurement.

Extension cable

Handy for using the photoreceptor and the display unit separately.
5 types available:
2m (ZV-21), 5m (ZV-22),
10m (ZV-23), 20m (ZV-24),
and 30m (ZV-25).



Bright Loader (by Harvey lab)



Count	in	Range
1	0.000E+00	3
2	0.000E+00	3
3	0.000E+00	3
4	0.000E+00	3
5	0.000E+00	3
6	0.000E+00	3
7	0.000E+00	3
8	0.000E+00	3
9	0.000E+00	3
10	0.000E+00	3

Bright Loader is data collection software to retrieve measured data from UVR-300. Measurement interval, the number of measurement, and Measurement range can be specified via PC. Integral illuminance can be calculated. Measured data is saved as CSV format, which can be open by spreadsheet program. Mini USB cable is required to connect PC to UVR-300.

• OS : Windows 2000 / Windows XP / Windows Vista (32bit)



*Some screens are simulated.
*The specifications and external appearances of product in this catalogue may be changed without prior notice due to improvements.
*The catalogue includes products that are sold separately.
*The actual color of products may differ slightly from the catalogue due to lighting and printing conditions.

Contact information:

TOPCON TECHNOHOUSE CORPORATION

75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580 JAPAN
Phone: +81-3-3558-2666 Fax: +81-3-3558-4661
E-mail: techno-info@topcon.co.jp

SAFETY PRECAUTIONS



Make sure to carefully read the "Manual" to ensure that you use the product properly and safely.
• Always connect the instrument to the specified power supply voltage.
Improper connection may cause a fire or electric shock.
• Be sure to use the specified batteries.
Using improper batteries may cause a fire or electric shock.

For more information please visit our website.

<http://www.topcon-techno.co.jp/en/>

