

Insert Tube Options


Cast probe



- Side view



- Snapshot
- brightness+
- brightness -



Features	39DF-1M-ST front view probe	39DS-1M-ST side view probe
Probe head diameter	3.9 mm	3.9 mm
Probe head length	5.6 mm	7.6 mm
Probe head material	Stainless steel	Stainless steel
Probe diameter	3.9 mm	3.9 mm
Probe length	1 m	1 m
Pobe material	Spring, stainless steel	Spring, stainless steel
LED	Front	Side
DOF	5 mm~60 mm	2 mm~30 mm
FOV	90°	90°
Working temperature	-10°C to 60°C	-10°C to 60°C
Storage temperature	-10°C to 60°C	-10°C to 60°C
Resolution	400*400	400*400
Button	Snapshot, Brightness+, Brightness-	Snapshot, Brightness+, Brightness-



Features	39DF-1M-SR
Probe head diameter	3.9 mm
Probe head length	12 mm
Probe head material	Stainless steel
Probe length	1 m
Probe material	Steel, semirigid
LED	Front / Side
DOF	10 mm~60 mm
FOV	90°
Working temperature	-10°C to 60°C
Storage temperature	-10°C to 60°C
Resolution Pixels	400*400
Button	Snapshot, Brightness+, Brightness-