

LED illuminated magnifier

OLIGHT3L series

A high-grade model that adds contrast power from one-way lighting to a rectangular lens with little distortion.

AR Coat
selectable



RECTA LENS

2X

3.5X

2XAR

3.5XAR

Select the lens magnification and combine it with the main unit.

Example: **OLIGHT3L-F 2X AR**

Series name Type name Magnification

We also sell only the main body without a lens.

- Lens Dimensions (mm) : 144×108
- Lineup of AR-Coated lens : option
- Dimming function : 100% - 50%
- Input voltage range : AC100 - 240V* · 50/60Hz
(* When using at a voltage of 125V or higher, it can be handled by changing the cord with a plug.)
- Power Cord length (mm) : 1800

OLIGHT3L Series features.

The OLIGHT3L series features a diagonally-mounted white LED lighting panel to emit light at an angle in relation to the lens center. This means the product is designed with an emphasis on rendering unevenness on work-pieces visible. The model excels at detecting surface scratches and dents, etc. on metal and resin. The rectangular lens has reduced peripheral distortion to handle extended work periods. The product can reduce strain and fatigue from work through the use of optional AR-Coated Lenses which suppress refraction, increasing the volume of light that passes through.



Lineup

OLIGHT3L-B

With table stand

Product Dimension (WxHxD): 185x380x300mm

Weight: 2.3kg (Excluding lens)




OLIGHT3L-F

Free arm and clamp type

Product Dimension (Arm length) : 905mm

Weight: 2.5kg (Excluding lens)



OLIGHT3L-FD

Free arm and fixed, desk holder type

Product Dimension (Arm length) : 940mm

Weight: 2.4kg (Excluding lens)

